

IDG-BC5100S

Standalone Keypad Access Control

Features

- + Indoor use
- + Can connect external reader
- + Full programming from the keypad
- + 2000 uses, supports Card, PIN, Card + PIN
- + Can be used as a standalone keypad
- + Backlight keys
- + Wiegand 26 output for connecting to a controller
- + Wiegand 26 input for connecting with a reader
- + Adjustable Door Output time, Alarm time, Door Open time
- + Very low power consumption (30mA)
- + Fast operating speed, <20ms with 2000 users
- + Lock output current short circuit protection
- + Easy to install and program
- + Built in light dependent resistor (LDR) for anti tamper
- + Built in buzzer
- + Red, Yellow and Green LEDES display the working status

Specifications

Operating Voltage	DC 12V±10%
User Capacity	2000
Card Type	EM
Card Reading Distance	5-8 cm
Active Current	<60mA
Idle Current	25±5mA
Lock Output Load	Max 3A
Alarm Output Load	Max 20A
Operating Temperature	-45°C~60°C
Operating Humidity	10%- 90% RH
Adjustable Door Relay time	0 -99 seconds
Adjustable Alarm Time	0- 3 minutes
WG Interface	WG26 bits
Wiring Connections	Electric Lock, Exit Button, External Alarm & Reader
Dimensions	L96 x W73x H20 mm

Dimensions

