

VTO1210A-X

Apartment Outdoor Station



| Technical Specification | |
|--------------------------------|-------------------------------------|
| Model | VTO1210A-X |
| System | |
| Main Processor | Embedded Micro Processor |
| Operation System | Embedded LINUX OS |
| Video | |
| Video Compression | H.264 |
| Image Sensor | 1/3" 1.3MP CMOS |
| Lens | 3.6mm |
| Angle of View | D:95° H:75° |
| Day/Night | Color Image |
| Audio | |
| Audio Compression | G.711 |
| Audio Input | Omnidirectional Mic |
| Audio Output | Built-in Speaker |
| Bidirectional Talk | Support Dual-way Bidirectional talk |
| Display | |
| LCD Screen | 3" STN 128x64 |
| Operation Mode | |
| Keypad | Mechanical Button |
| Reader | Mifare Card |
| Approaching Induction | |
| Body approaching | - |
| Interface | |
| Door Control | 1 |
| | |

Features

- 10-inch IPS touch screen
- · Night vision
- · Unlock via password, card, fingerprint and remotely unlock
- · Aluminium alloy plate, IP 54
- · Heating inside, allow working environment down to-40 °C
- · Expand face recognition















| Alarm In | 2(1ch unlock button, 1ch feedback) |
|------------------|------------------------------------|
| RS485 | 1 |
| Network | |
| Ethernet | 10M/100Mbps |
| Network Protocol | TCP/IP |
| General | |

| General | |
|---------------------|------------------------|
| Ingress Protection | IP54 |
| Tamper Switch | 1 |
| Installation | Flush |
| Material | Aluminum |
| Power | DC 12V |
| Power Consumption | Standby ≤1W, Work ≤10W |
| Working Temperature | -40°C~+60°C |
| Relative Humidity | 10%~90%RH |
| Dimensions | 151.0mm×376.0mm×59.1mm |
| Weight | 1.6Kg |

View Area Dimensions





Application

