

VTH5221D/DW

Wi-Fi Indoor Monitor



Technical Specification

Model	VTH5221D/DW
-------	-------------

System

Main Processor	Embedded Micro Processor
----------------	--------------------------

Operation System	Embedded LINUX OS
------------------	-------------------

Video

Video Compression	H.264
-------------------	-------

Audio

Audio Compression	G.711
-------------------	-------

Audio Input	All-direction Microphone
-------------	--------------------------

Audio Output	Built-in Loudspeaker
--------------	----------------------

Bidirectional Talk	Support Dual-way Bidirectional talk
--------------------	-------------------------------------

Display

LCD Screen	7" 1024x600, Capacitive
------------	-------------------------

Operation Mode

Input	Touch buttons
-------	---------------

Interface

Alarm In	6
----------	---

Alarm Out	1
-----------	---

RS485	1
-------	---

Network

Wi-Fi	IEEE802.11b/g/n
-------	-----------------

Ethernet	10M/100Mbps Self-adaptive
----------	---------------------------

Network Protocol	TCP/IP
------------------	--------

General

Memory Slot	Micro SD, Max 32GB
-------------	--------------------

Features

- 7" TFT Capacitive touch screen, 1024x600
- IPC surveillance
- Alarm integration
- Micro SD card optional, max 32GB
- Record & Snapshot(SD card needed)




General

Memory Slot	Micro SD, Max 32GB
Installation	Surface
Power	DC 12V, PoE (802.3af)
Power Consumption	Standby ≤1W, Work ≤7W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	215.0mm×140.0mm×21.0mm
Weight	0.8Kg

Dimensions



View Area



Application

