



Features & Function

- ▶ Up to 2 cameras, 2 monitors and 2 interphones
- Monitoring a entrance
- ► Talk with a visitor
- Door lock reselase
- Intercom fucntion (DP-4VHP)
- LED backlight



CDV-70P

COMMAX CDV-70P is show up! It's a world famous products that has upgraded with new design and new ability. It will be the greatest product in the world beyond CDV-70P





DP-4VHP



DRC-4MC

Icons

• Monitor	
• Interphone	•
• Talk	

Open	
------	--

Speci	fication					
Model		DP-4VHP		DRC-4MC		
Transmission way		Door camera 4 wires (Polarity), interphone 4 wires (Polarity)		4 wires to a monito 2 wires to the door	r (Polarity), release (non-polarity)	
Rating Vo	Itage	100V-240V~, 50/60Hz (FREE VOLTAGE)		- 0 -		
Power Co	onsumption On stand-by: 3.5W On talk: 15W		DC 12V (Supplied from monitor)			
Transmiss	sion way	HANDS FREE (Voice switch circuit)		-)		
Monitor		7" TFT-DIGITAL LCD		-		
Call sound	d	Door: Electronic chime (Sol Mi Do), interphone: Beep		-		
Display		Monitoring: 30 ± 5sec, Talk: 60 ± 5sec		-		
Minimum Illumination -		0.1 Lux (within 300mm)				
Effective \	ve Viewing Angle -		Horizontal 68°, Vertical 50°			
Angle Adjustment -		Up, down 12 Degrees				
Distance	Diameter (pie)	0.5	0.65		0.8	
	Diameter (meter)	28m	50m		70m	
Working temperature 0 ~+40°C (32°F ~ 104°F)			-10°C ~+40°C			
Dimension		243.0(W) X 168.0(H) X 30.0(D)		96(W) X 155(H) X 325(D)		

